

## REMARKS

In view of the above amendments and the following remarks, reconsideration of the objections and rejections and further examination are respectfully requested.

As an initial matter, Applicants request that the Examiner return a fully initialed copy of the PTO-1449 Forms which were filed as part of the Information Disclosure Statements of May 23, 2006 and August 1, 2007.

The specification and abstract have been reviewed and revised to improve their English grammar. The amendments to the specification and abstract have been incorporated into a substitute specification and abstract. Attached are two versions of the substitute specification, a marked-up version showing the revisions, as well as a clean version. No new matter has been added.

Claims 1-20 have been cancelled without prejudice or disclaimer of the subject matter recited therein and replaced by claims 21-37.

Claims 1-20 were objected to for various informalities identified by the Examiner. These objections are not applicable to new claims 21-37. Thus, withdrawal of this objection is respectfully requested.

Original claims 1-9 and 13-18 were rejected under 35 U.S.C. § 101 for failure to recite statutory subject matter (i.e., for reciting software alone). Claims 1-20 have been cancelled in favor of new claims 21-37. Claims 21-37 comply with 35 U.S.C. § 101. Thus, it is respectfully submitted that this rejection is not applicable to new claims 21-37.

Claims 1-20 were rejected under 35 U.S.C. § 102(e) as being anticipated by Simpson (U.S. 6,944,868). This rejection is believed clearly inapplicable to new claims 21-37 for the following reasons.

New independent claim 21 includes recitations directed to a safe service extension receiving apparatus including a receiving section, an executing section, and a service extension section. Claim 21 recites that the receiving section is for receiving an execute form including (i) a service-dependent Application Program Interface (API) for extending services associated with the received execute form, (ii) a Capi for calling the service-dependent API, and (iii) service identification information for associating the received execute form with a service. Claim 21 recites that the service extension section is for extending the services associated with the received execute form, the services associated

with the received execute form only being extended by calling the service-dependent API included in the received execute form, and the service-dependent API only being called according to the Capi included in the received execute form. Finally, claim 21 recites that the executing section is for executing the services associated with the received execute form. The Simpson reference does not disclose or suggest the above-mentioned features of independent claim 21.

Rather, Simpson teaches implementing an imaging extension 22 in a browser, wherein the image extension 22 is stored on a user's computer 12 which receives and executes web content 16 received from a web server 30 (see Abstract, Fig. 1, and col. 8, lines 4-13). Further, Simpson teaches that the imaging extension 22 is an API used to gain access to the personal imaging repository 50 of the user's computer 12, wherein the imaging extension 22 gains the access in response to generic access instructions (see Fig. 1, col. 8, lines 14-21).

Thus, in view of the above, it is clear that Simpson discloses that the image extension API is stored on the user's computer 12 which executes the web content, but does not disclose or suggest that (i) the received execute form includes the service-dependent API which extends the services associated with the received execute form and (ii) the received execute form including the API is executed by the apparatus which received the API, as required by claim 21.

Further, in view of the above, it is clear that Simpson discloses that the API stored on the computer is used to gain access to a personal repository of the computer, but does not disclose or suggest extending services associated with the received execute form, as recited in claim 21.

Finally, in view of the above, it is clear that Simpson discloses, that in response to generic access instructions, the API stored on the computer is utilized, but does not disclose or suggest that the services associated with the received execute form are extended only by calling the service-dependent API included in the received execute form, wherein the service-dependent API is only called according to the Capi included in the received execute form. Therefore, because of the above-mentioned distinctions, it is clear that Simpson does not anticipate new independent claim 21.


Furthermore, neither Simpson nor any of the prior art of record suggests the above-discussed limitations of claim 21. Therefore, it would not have been obvious to one of ordinary skill in the art to modify Simpson so as to obtain the invention of new claim 21. Accordingly, it is respectfully submitted that new claim 21 and claims 22-35 which depend therefrom are clearly allowable over Simpson.

New independent claims 36 and 37 are method and program claims which recite features similar to those set forth in claim 21 (i.e., receiving execute form, extending the services associated with the received execute form, and executing the services associated with the received execute form). Thus, for reasons similar to those discussed above, it is respectfully submitted that claims 36 and 37 are allowable over the Simpson reference.

In view of the above amendments and remarks, it is submitted that the present application is now in condition for allowance and an early notification thereof is earnestly requested. The Examiner is invited to contact the undersigned by telephone to resolve any remaining issues.

Respectfully submitted,

Mitsuteru KATAOKA

By:   
Andrew L. Dunlap  
Registration No. 60,554  
Attorney for Applicant

ALD(JRF)/nrj  
Washington, D.C. 20006-1021  
Telephone (202) 721-8200  
Facsimile (202) 721-8250  
December 6, 2007

DESCRIPTION

SAFE SERVICE EXTENSION PLATFORM

5

BACKGROUND OF THE INVENTION

1. Field of the Invention~~TECHNICAL FIELD~~

The present invention relates to a service-extensible, completely new "safe service extension platform" which realizes new dimensional safety in which false access by an execute form which implements a digital content providing service can be eliminated without the need to deny that a process which might cause the false access is included in the execute form. Specifically, it relates to a safe service extension platform which is capable of eliminating false access, such as a change of the status of another service, data corruption, and a system down of the platform itself, without the need of inference from the authenticity of the distributor of an execute form, while capable of changing or adding an execute form to achieve service extension, such as a change of a service function/feature or an addition of a new service.

2. Background of the Related Art~~BACKGROUND ART~~

As described above, the present invention provides an unprecedented completely new "safe service extension platform",

and therefore it is considerably difficult to give a suitable example thereof that should be given as a conventional art. ~~Accordingly, firstly~~ Initially, three major features unique to the safe service extension platform which is believed to be proposed  
5 first by the present invention are described below. A first feature is service extensibility; a second feature is the assurance of safety; and a third feature is achievement of a seamless service extension operation.

The first feature "service extensibility" means that a  
10 different user interface is provided for each service, and a change of the user interface or an addition of an unexpected service can be carried out at any time. The second feature "assurance of safety" means that the safety is assured without the need to deny that a process, which might cause false access, is included in  
15 an execute form. The third feature "achievement of a seamless service extension operation" means that the operational procedure for service extension can be carried out with the same operational feeling as the operational feeling in utilizing the service.

As described above, the "safe service extension platform"  
20 which satisfies all of the three major features cannot be found in conventional art. However, if a conventional art example is required, a push-type service via the Internet which involves the use of a personal computer can be cited as satisfying only the first feature. PointCast(R) of PointCast Network is a push-type  
25 service which realizes a news distribution service. The

utilization of a plurality of push-type service which involves the use of a personal computer is made possible by installing a browser, which is written in machine language and executed for each service, to the personal computer.

5        Here, the first feature of the present invention, i.e., the "service extensibility", is described in conjunction with the push-type service. A new service can be added by installing a browser, which executes a push-type service, to a hard disk of a personal computer. The browser is a computer program written  
10 in machine language, and provides a unique and different user interface for each service.

The installation of the browser is conventionally carried out as described below. For example, the browser is installed by firstly activating a file transfer protocol (e.g., ftp) client  
15 to download the browser to the client's hard disk, and then activating the downloaded browser. Also, before using a new browser, the browser's settings are operated with a setting menu incorporated in the browser.

The second feature of the present invention, i.e., the  
20 "assurance of safety", is conventionally based merely on speculation, and is not supported by a specific plan. Specifically, the safety of a browser is conventionally based merely on a desire that a malicious third party has not caused the browser to be infected with a computer virus or the like since the browser is obtained  
25 through a formal distributor, such as an official home page.



As for the third feature of the present invention, i.e., the "achievement of a seamless service extension operation", which means a high-level presentation function by a service, in conventional art, a different user interface is realized by changing a browser for each service, resulting in satisfaction of the requirement that different user interfaces are provided for a plurality of services, which is necessary to partially achieve a seamless operation.

Referring to FIG. 18, a conventional service-extensible service platform, which is not safe as described above, is described in detail. As shown in the figure, a conventional service platform *PFC* includes a service provision source 1610, a delivery system 120, and a terminal device 1630. The service provision source 1610 includes an execute file provider 1111 and a file transfer server 1611. The execute file provider 1111 may be a hard disk drive having an execute file stored therein. The file transfer server 1611 may be a Web server. As will be described later with reference to FIG. 19, the execute file is binary data, typified by a program file which is directly passed to an OS of the terminal device 1630 and executed.

The delivery system 120 transfers an execute file, which is transmitted from the service provision source 1610, to a terminal device 1630 which is spatially and temporally away therefrom.

The terminal device 1630 includes an executor 1133 and an execute file storage device 1132. The executor 1133 activates

an execute file stored in the execute file storage device 1132 to execute any process in the terminal device 1630. For example, in the case of activating a file transfer program as an execute file, an execute file for executing a new service, which is received  
5 via the delivery system 120, is stored into the execute file storage device 1132. Also, a service can be provided to the user by executing the execute file which executes the service.

FIG. 19 shows by way of example data stored in the execute file storage device 1132 of the service platform *PFc*. In addition  
10 to *FE(S1)*, which is an execute file for service *S1*, and *FE(S2)*, which is an execute file for service *S2*, the execute file storage device 1132 has stored therein execute file *FE(shell)* for a shell for providing a user interface for platform operation, such as activation of an execute file, and *FE* (file transfer) which is  
15 a file transfer program for introducing execute file *FE* for executing a new service to the terminal device 1630 via the delivery system. Any of these execute files can be implemented in machine language.

FIG. 20 shows software hierarchy in the service platform  
20 *PFc*. As can be seen from the figure, in the service platform *PFc*, any execute files for executing any services can be newly introduced by activating the file transfer execute file. In this manner, an application layer is composed of execute files immediately above an OS layer composed of an OS (Operating System). As a result,  
25 a service-implementing execute file is able to directly reference



and control the resource of the OS. Accordingly, the OS is vulnerable to a malicious execute file, and therefore it cannot be said that the service platform *PFC* is safe.

As for the first feature of the present invention, i.e.,  
5 the "service extensibility", it is possible to simply introduce a new service, but conventionally it is not possible to introduce a new service which is seamlessly related to the content viewing as presented by the present invention. That is, the operability in the content viewing and the operability in the introduction  
10 of a new service are completely different from each other both in appearance and in procedure. For example, conventionally, in order to install a browser, it is necessary to activate a file transfer protocol client to download the browser to the client's hard disk, and to activate the downloaded browser. Also, before  
15 using a new browser, it is required to set the browser by operating a setting menu whose degree of usability is completely different from the degree of usability of a content viewing window of the browser.

Also, conventionally, functionality extension is carried  
20 out by using a user interface common to all services. Accordingly, the number of entries of various parameters (an installation destination directory, a user name, etc.) required for installing a program for service extension becomes a logical sum of parameters required for all services. Therefore, when installing a specific  
25 service extension program, there is a possibility that the user

might be required to enter a basically unnecessary parameter.

In contrast, flexible service extensibility provided by a safe service extension platform according to the present invention realizes service extension with the same operational usability  
5 as the content viewing without closing a browser or carrying out a procedure whose usability is completely different from that of the content viewing. That is, it achieves the situation where service extension is carried out as an extension of a normal operation with the same usability as the usability of the content  
10 viewing with which the user is most familiar, and without causing the user to carry out operation with the usability specific to the service extension. However, as described above, such extensibility cannot be provided by a conventional service platform, and therefore there is a need for a method for realizing completely  
15 new service extension.

As for the second feature of the present invention, i.e., the "assurance of safety", in fact, it is not so rare that even in a browser obtained through an official distributor, a bug adversely affects the operation of another push-type service, or  
20 causes the entire system to go down. ~~Accordingly~~Thus, conventionally, it is necessary to assure that the binary data of the browser is valid, i.e., the binary data of the browser does not include a false access process. However, the assurance is based only on a trust-based relationship, and is not intended to  
25 ensure that the binary data of the browser includes no false access

process.

On the other hand, the safety provided by the safe service extension platform according to the present invention is completely new dimensional safety in which execution of any execute form  
5 (corresponding to the browser in the exemplary conventional art) does not adversely affect another service nor cause the entire system to go down. In the conventional art, as a matter of course, such a scheme does not exist, and therefore there is a need for a completely new execution method.

10 Further, as for the third feature of the present invention, i.e., the "achievement of seamless service extension operation" which executes a high level presentation function, in the conventional art, it is not possible to establish a seamless relationship between service management and content viewing.  
15 This is because the service management is carried out with the setting menu of the browser. That is, operation related to the service management cannot be carried out in the content viewing window.

On the other hand, in a high level presentation function  
20 by the service provided by the safe service extension platform according to the present invention, content includes service settings. Therefore it has a high level representation equivalent to that of the content, and a server is able to freely set the details of presentation with the same usability of that of the  
25 content viewing.

For example, by combining a service setting function with a content using a high level description capability of, for example, filling out a questionnaire and returning it to the server, whereby the user answers the questionnaire for the user's interest, it is made possible to achieve a high level presentation function of setting user preference information for automatically selecting content. Also, the user is able to carry out a high level setting with a simple operation without being aware of when the content ends and the service setting begins.

10 In the conventional art, as a matter of course, there is no method for executing a high level presentation function by the service presented by the safe service extension platform according to the present invention.

Therefore, an object of the present invention is to provide a safe service extension platform which realizes the above three features.

#### ~~DISCLOSURE~~ BRIEF SUMMARY OF THE INVENTION

To achieve the above object, the present invention has the following aspects.

A first aspect of the present invention is directed to a safe service extension platform in which services are associated with an execute form, and the services are extended by changing or adding the execute form, the platform comprising a service-dependent API for extending the services, wherein the

service extension from the execute form is carried out only by calling the service-dependent API.

Thus, in the first aspect, it is possible to ensure that the safety ~~which~~ is not affected by whether the execute form is authentic.

In a second aspect based on the first aspect, the service extension is to provide a new service.

In a third aspect based on the first aspect, the service extension is to start using a service.

In a fourth aspect based on any one of the first, second, and third aspects, the extension of a target service is carried out only by calling the service-dependent API from an execute form associated with the target service.

In a fifth aspect based on any one of the first, second, and third aspects, a parent/child relationship is defined between a plurality of services. When, ~~and in the case where~~ a call for the service-dependent API is requested by the execute form and designates, as a process target, -a service-dependent resource associated with a service, only when a service associated with the execute form is an ancestor of that service, service-dependent resource can be processed.

In a sixth aspect based on any one of the first, second, and third aspects, an execute form associated with a metaservice at least one of the services can be extended by the service-dependent API.

In a seventh aspect based on the sixth aspect, in the case of the execute form associated with the metaservice, all of the services can be extended by the service-dependent API. In,~~and~~ in the case where the execute form (DE) is not associated with the metaservice, the service-dependent API is unable to extend the services.

In an eighth aspect based on any one of the first, second, and third aspects, the execute form is a control content which satisfies requirements that are to be satisfied by contents, the control content (DC) is transmitted as a content together with at least one of the contents, information for designating the control content from at least one of the contents, and the service-dependent API can be processed only by the control content.

In a ninth aspect based on the eighth aspect, the service-dependent API controls automatic storage of a specific service content (DC).

In a tenth aspect based on any one of the first, second, third, fourth, fifth, sixth, seventh, eighth, and ninth aspects, the execute form is sent from at least one service provision portion, and received by at least one terminal device for executing the execute form.

Note that in one embodiment of the present aspect, the service extension can be carried out with the same operational usability as the content viewing without closing a browser or carrying out a procedure whose usability is completely different from that of

the content viewing. That is, it achieves the situation where service extension is carried out unknowingly with the same usability as the usability of the content viewing with which the user is most familiar, and without causing the user to carry out  
5 an operation with the usability specific to the service extension.

Also, it is possible to achieve completely new dimensional safety in which execution of any execute form (corresponding to the browser in the exemplary conventional art) does not adversely affect another service nor cause the entire system to go down.

10 Further, in another embodiment, content includes service settings. Therefore it has a high level representation equivalent to that of the content, and it is a function which allows a server to freely set the details of presentation with the same usability of that of the content viewing. Also, the user is able to carry  
15 out a high level setting with a simple operation without being aware of when the content ends and the service setting begins.

#### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a block diagram schematically showing the structure  
20 of a safe service extension platform according to a first embodiment of the present invention.

FIG. 2 is a diagram for explaining an identified execute form stored in an identified execute form storage device of the safe service extension platform shown in FIG. 1.

25 FIG. 3 is a diagram for explaining a service-dependent



resource management table managed in a service-dependent resource manager of the safe service extension platform shown in FIG. 1.

FIG. 4 is a flowchart showing a new service registration/management operation by the service-dependent resource management of the safe service extension platform shown in FIG. 1.

FIG. 5 is a flowchart showing a service execution operation by a terminal device of the safe service extension platform shown in FIG. 1.

FIG. 6 is a diagram for explaining a software hierarchy of a terminal device of the safe service extension platform shown in FIG. 1.

FIG. 7 is a diagram for explaining an exemplary screen image presented to the user by the safe service extension platform shown in FIG. 1.

FIG. 8 is a block diagram schematically showing the structure of a safe service extension platform according to a second embodiment of the present invention.

FIG. 9 is a diagram for explaining an identified execute form and a meta service execute form which are stored in an identified execute form storage device of the safe service extension platform shown in FIG. 8.

FIG. 10 is a flowchart showing a service execution operation by a terminal device of the safe service extension platform shown in FIG. 8.

FIG. 11 is a block diagram schematically showing the structure of a safe service extension platform according to a third embodiment of the present invention.

FIG. 12 is a diagram for explaining an identified execute form and a parent/child identified execute form which are stored in an identified execute form storage device of the safe service extension platform shown in FIG. 11.

FIG. 13 is a flowchart showing a service execution operation by a terminal device of the safe service extension platform shown in FIG. 11.

FIG. 14 is a block diagram schematically showing the structure of a safe service extension platform according to a fourth embodiment of the present invention.

FIG. 15 is a diagram for explaining a control content and a content which are stored in a content storage device of the safe service extension platform shown in FIG. 14.

FIG. 16 is a diagram for explaining a service-dependent resource management table managed in a service-dependent resource manager of the safe service extension platform shown in FIG. 14.

FIG. 17 is a flowchart showing a control content execution operation by a terminal device of the safe service extension platform shown in FIG. 14.

FIG. 18 is a block diagram schematically showing the structure of a conventional service platform in conventional art.

FIG. 19 is a diagram for explaining an execute file stored

in an execute file storage device of the service platform shown in FIG. 18.

FIG. 20 is a diagram for explaining a software hierarchy of a terminal device of the service platform shown in FIG. 18.

5

~~BEST MODE FOR CARRYING OUT~~DETAILED DESCRIPTION OF THE INVENTION

Firstly, the basic concept of a safe service extension platform according to the present invention is described. In the safe service extension platform according to the present invention, a service is structured as an execute form which is configured as a so-called script, which is interpreted by an executor for instructing execution of an OS, rather than as, for example, a binary execute file which is directly executed by the OS as is conventionally the case. The execute form includes an API call, and is associated with a predetermined service.

The API is service-dependent, and when it is called, it behaves in a manner dependent on the associated service. The service-dependent API processes a resource specific to the service associated with the execute form in which the API is included. Also, any process which the execute form performs on the resource is restricted so as to be performed via an API, and there is no API, other than service-dependent APIs, which processes the resource processed by the service-dependent APIs. Also, a set of APIs written in the execute form are previously prepared commonly for all services, and they are identical to each other.

With this structure, it is possible to secure new dimensional safety, which does not depend on the authenticity of an execute file in the conventional art (or an execute form in the present invention), and to create a service-extensible, completely new "safe service extension platform". In this platform, by operating a browser, which is an example of an execute form for executing a service, it is made possible to view content which is an instance of a service. Ordinary content viewing is executed by sequentially calling APIs included in the content. Therefore, the execute form (browser) includes a service-dependent API which is a kind of API. Thus, the service is extended by calling the service-dependent API during the content viewing. As a result, in the present invention, the user sees the service extension as a content viewing operation.

The user interface for service extension is determined by the execute form including service-dependent APIs. By associating the execute form with services, it is made possible to extend each service using a user interface suitable for that service.

The user interface for service extension can be optimally configured for each service. For example, in the case of a push-type service/storage-type broadcasting service, a contract for a premium service subscribable only by specific members among all members of the service can be solicited only from the specific members through the use of an ordinary service content. Since

the user interface can be sufficiently customized in accordance with the purpose thereof, solicitation for services can be carried out in a more appropriate and stronger manner.

If the present invention is applied to a Java application  
5 (i-appli or the like) which is used in mobile telephones, etc.,  
by writing a program for extending a service function in application  
software for executing a service to which the user subscribes,  
it is possible to execute a functional extension of the service.  
For example, an operation of extending an i-appli function, such  
10 as a skin, as a plug-in can be executed by the i-appli itself.

Further, by writing a conditional judgment in content with  
a script included in the content, such that an API is called, which  
in response to a question, returns a character string representing  
the model number of a receiver or the type of a manufacturer, it  
15 is made possible to change a user interface for each receiver model  
number or for each manufacturer.

Also, if it is applied to a pay-per-view program in digital  
broadcasting, by writing algorithm suitable for distributed  
content, it is possible to manage a time period or channel for  
20 which free introductory viewing is possible by using the algorithm  
programmed in the content. In the case of the pay-per view program  
in the digital broadcasting, a contract for a pay-per-view service  
can be made through data broadcasting on a pay-per-view channel.  
Also, it is possible to provide a service, which varies from one  
25 user to another and leads to contract promotion, in such a manner

that only the user who achieves a high score in a game on data broadcasting can hold a service contract at low price.

Further, if content is programmed so as to execute a service-dependent API, the user performs a predetermined operation  
5 on the content, thereby performing seamless service extension on the content without losing the content's description capability.

For example, in the case of installing a plug-in for a Web browser, it is possible to install the plug-in at the time of reception of content without accessing a download page of the  
10 development vender of the plug-in in order to obtain an install program for the plug-in. Also, the user is not required to be familiar with trade names of plug-ins for the Web browser, and content can be executed by selecting the description of the content itself, such as "a moving image of a product viewed from a 360-degree  
15 angle".

Also, if it is applied to an electronic book player or a PDA, it is possible to provide a function of, when a specific home page is entered, automatically preparing a browser, which is exclusively used for displaying a bulletin board required by the  
20 home page, without being noticed by the user. That is, user interfaces for use in content viewing and service extension can be configured seamlessly. Since the service extension can be carried out using a user interface with the same operational usability as the content viewing, the load on the user is  
25 insignificant.

Further, if service-dependent APIs are added as APIs that are to be sequentially executed, the service-dependent APIs can be sequentially executed similar to other APIs by executing the execute form. As a result, it is possible to program the execute  
5 form so as to automatically execute the service extension. Also, if full automation is achieved, it is possible to execute temporary service extension, such as an exclusive service for use during traveling or a free trial, without making the user aware of it.

For example, in the case of an electronic book player or  
10 a PDA, it is possible to provide a title with a screen effect for page turning as a bonus plug-in which is only usable with that title. Also, it is possible to automatically utilize an on-the-spot service, such as a virtual guide to facilities at Narita airport.

15 Further, in the present invention, it is ensured that the service extension is carried out with the same operational usability as the content viewing without closing a browser or carrying out a procedure whose usability is completely different from that of the content viewing. Specifically, it is possible  
20 to provide an environment where a service extension is carried out without the user being aware of it and with the same usability as the usability of the content viewing with which the user is most familiar, so that the user is not caused to carry out operation with the usability specific to the service extension.

25 For example, in the case of a push-type service/storage-type



broadcasting service, it is not necessary for the user to be accustomed to usage of a plurality of user interfaces, e.g., downloading after activating an upgrading function of a viewer in order to upgrade the viewer itself, or a Web browser in order  
5 to introduce another service.

Therefore, even in the case where it is necessary to properly use a plurality of browsers depending on the details of content or the user's preferences, the user is not required to become accustomed to different levels of operability of various user  
10 interfaces. Accordingly, even an unaccustomed user can be reassured and readily carry out functional extension. Moreover, once a viewing device is shipped, the user interface is not permanently fixed and the operability thereof can be improved depending on the user's preferred level of usability.

15 Further, it is common to all aspects to ensure completely new dimensional safety in which execution of any execute form (corresponding to the browser in the exemplary conventional art) does not adversely affect another service nor cause the entire system to go down.

20 (First Embodiment)

Referring to FIGs. 1, 2, 3, 4, 5, 6, and 7, a safe service extension platform according to a first embodiment of the present invention is described. As shown in FIG. 1, a safe service extension platform *SEPl* according to the present embodiment  
25 includes a service provision source 110, a delivery system 120,

and a terminal device 130.

The service provision source 110 sends out an execute form for executing a new service that is to be executed by the terminal device 130. The delivery system 120 temporally and/or spatially transfers information sent from the service provision source 110 to the terminal device 130. The delivery system 120 can be composed of an internet communications network, a broadcasting or communications radio network, or a combination of a package medium, such as a DVD-ROM (Digital Versatile Disk-Read Only Memory), and a physical logistics system.

The terminal device 130 uses the information received via the delivery system 120 to execute the service provided by the service provision source 110, and provides an execution result to the user. Note that in FIG. 1, for the sake of simplification, the service provision source 110, the delivery system 120, and the terminal device 130 are illustrated such that the ratio in number of them is 1:1:1. However, the ratio in number may be 1:1:c (where c is an arbitrary natural number) similar to the ratio seen in a broadcast topology, may be a:1:c (where a is an arbitrary natural number) in the case of the Internet or the like, or may be a:b:c (where b is an arbitrary natural number) in the case where there are a plurality of delivery systems. Such generalization is applicable to all embodiments as described below.

The service provision source 110 includes an execute form provider 111, a service identification setter 112, and a sender

113. The execute form provider 111 has stored therein execute forms for executing services, and outputs them if the necessity arises. The execute forms may be SGML (Standard Generalized Markup Language)-based/XML (eXtensible Markup Language)-based markup languages, such as HTML languages (HyperText Markup Languages) for use in the Internet, BML languages (Broadcast Markup Languages) for use in data broadcasts in Japanese digital broadcasting, or may be Java(R) languages or machine languages which operate on a virtual machine. Note that it is so configured that the execute forms are passed to an OS of the terminal device 130 via an executor, which is provided in the terminal device 130 as will be described later, and executed by the OS.

The service identification setter 112 generates associated information *IS* about execute form *DE* outputted from the execute form provider 111, which indicates a subsidiary matter, such as an attribute of the execute form *DE*, and adds it to the execute form *DE* to generate identified execute form *DEi*. The associated information *IS* includes service identification information *Es*, which is information for associating with a service that is to be executed by a corresponding execute form *DE*, and subsidiary information  $\alpha$ , which indicates information about conditions and status of use of the execute form *DE* and the details of a corresponding service. For example, the service identification information *Es* may be an ID, which is a unique number, or may be a name. The subsidiary information  $\alpha$  may be either a text or a

code. Also, the identified execute form *DEi* may be generated such that the execute form *DE* and the associated information *IS* are integrated together, or they may be generated individually. In the present embodiment, the associated information *IS* is described  
5 by taking as an example a case where it is generated individually.

The sender 113 sends identified execute form *DEi* (execute form *DE* and associated information *IS*), which is inputted from the service identification setter 112, to the delivery system 120. A transmission model for realizing such sending may be either of  
10 the so-called pull- and push-types.

The pull-type refers to a transmission model which carries out sending in accordance with a demand from the terminal device 130 on the reception side, as can be seen in, for example, an HTTP (HyperText Transport Protocol) which is a transmission protocol  
15 for use in browsing homepages on the Internet. The push-type refers to a transmission model which carries out sending at a predetermined time regardless of a demand from the reception side, as can be seen in, for example, a DSM-CC (Digital Storage Media Command & Control) data carousel which is a transmission protocol for use  
20 in transmission in digital broadcasting.

The terminal device 130 includes a downloader 131, an identified execute form storage device 132, an executor 133, a resource selector 134, a general resource manager 135, and a service-dependent -resource manager 136. The downloader 131  
25 receives identified execute form *DEi* (execute form *DE* and

associated information *IS*), which is transmitted from the delivery system 120, and writes the received identified execute form *DEi* to the identified execute form storage device 132. The downloader extracts the associated information *IS* from the identified execute form *DEi*, and outputs it to the service-dependent resource manager 136. The associated information *IS* includes the service identification information *Es* which is set by the service identification setter 112 in a manner as described above. The downloader 131 is in conformity with a transmission model realized by the sender 113 and the delivery system 120, and can be executed in either case of a push-type or pull-type.

The identified execute form storage device 132 stores the identified execute form *DEi* (execute form *DE* and associated information *IS*) which has been written by the downloader 131. Also, in response to a demand, the identified execute form storage device 132 outputs the stored identified execute form *DEi* to the executor 133. The identified execute form storage device 132 can be composed of a storage medium, such as a hard disk drive (HDD) or a DVD-RAM, or a semiconductor memory such as flash memory or a RAM.

FIG. 2 shows how the identified execute form *DEi* is stored in the identified execute form storage device 132 accordance to the present embodiment. In this example, as for service *S1*, and services *S2* through *Sn* (where *n* is an arbitrary natural number), identified execute form *DEi(S1)* corresponds to the service *S1*, identified execute form *DEi(S2)* corresponds to the service *S2*,

and identified execute form  $DEi(Sn)$  corresponds to the service  $Sn$ .

The identified execute form  $DEi(S1)$  includes associated information  $IS(S1)$  consisting of service identification information  $Es(S1)$  and subsidiary information  $\alpha1$ , each of which  
5 corresponds to the service  $S1$ , and it also includes an execute form  $DE$ . Specifically, the service identification information  $Es(S1)$  associates the execute form  $DE$  with the service  $S1$ . Similarly, the identified execute form  $DEi(S2)$  includes associated  
10 information  $IS(S2)$  consisting of service identification information  $Es(S2)$  and subsidiary information  $\alpha2$ , each of which corresponds to the service  $S2$ , and it also includes an execute form  $DE$ . Further, the identified execute form  $DEi(Sn)$  includes associated information  $IS(Sn)$  consisting of service  
15 identification information  $Es(Sn)$  and subsidiary information  $\alpha n$ , each of which corresponds to the service  $Sn$ , and it also includes an execute form  $DE$ . The service identification information  $Es(Sn)$  associates the execute form  $DE$  with the service  $S2$ .

In the case where there is no need to individually distinguish  
20 between services, identified execute form  $DEi$  is represented as being composed of associated information  $IS$  consisting of service identification information  $Es$  and subsidiary information  $\alpha$ , and execute form  $DE$ . If it is necessary to individually distinguish between services, identified execute form  $DEi(So)$  is represented  
25 as being composed of associated information  $IS(So)$  consisting of

service identification information  $Es(So)$  and subsidiary information  $\alpha o$ , and execute form  $DE$ . Note that "o" is an arbitrary natural number less than or equal to  $n$ .

Referring back to FIG. 1, the executor 133 interprets execute  
5 form  $DE$  contained in identified execute form  $DEi$  inputted from the identified execute form storage device 132, and executes a service. As described above, the execute form  $DE$  contained in the identified execute form  $DEi$  stored in the identified execute form storage device 132 has a feature that in the terminal device  
10 130, it can be interpreted and executed by nothing other than the executor 133. The executor 133 executes interactive processes, such as input  $Iu$  by the user via an input device, such as a keyboard, a pointing device, or a speech input device, and output to an output device, such as a display in a GUI window or speech output, in  
15 accordance with a procedure based on the execute form  $DE$ .

If the execute form  $DE$  is a Java(R) language or a markup language, the executor 133 may be a virtual machine or an execution environment, which is generally called "browser". Alternatively, if the execute form  $DE$  is a machine language, the executor may  
20 be a middleware group, such as a library accompanying an OS for executing the execute form.

If an execute form  $DE$  that is to be interpreted and executed includes API (Application Program Interface) call  $Capi$ , the executor 133 uses the resource selector 134 to request the general  
25 resource manager 135 or the service-dependent resource manager



136 to issue the API call *Capi* for process execution. Also, the executor 133 notifies the service-dependent resource manager 136 of service identification information *Es* associated with the execute form *DE* that is currently being executed.

5       The resource selector 134 determines, based on the API call *Capi* issued by the executor 133, whether it is the general resource manager 135 or the service-dependent resource manager 136 that is being requested to carry out an API process. Then, the API call *Capi* is transferred to the one which has been determined as  
10   being requested. Note that the API call *Capi* is classified as a general API that is to be processed by the general resource manager 135 (hereinafter, referred to as a "general API") or as an API that is to be processed by the service-dependent resource manager 136 (hereinafter, referred to as a "service-dependent API").

15       The term "resource" refers to any computer resource which can be referenced, modified, or controlled by the terminal device 130 by means of the executor 133. Specifically, it includes a data structure stored in a primary storage device, such as a RAM, or a secondary storage device, such as a HDD, access right to a  
20   controllable input/output device, tangible input/output control, and communications control. Among these resources, a resource which can be processed without affecting another service is defined as a general resource, while a resource which exists for each service and is required to be processed for extending the service is defined  
25   as a service-dependent resource. An API for the general resource

is defined as a general API, while an API for the service-dependent resource is defined as a service-dependent API.

The following description is directed to exemplary relationships between two APIs and the same resource. It is assumed  
5 that one API refers to the resource and does not affect another service, while the other API modifies the resource and thus affects another service. In this case, the former corresponds to the general API, and the latter corresponds to the service-dependent API. In the following description, however, for simplification  
10 of the description, it is assumed that a resource for reference and a resource for modification are individually present and the former and latter are consistent in detail with each other.

As a specific example of the service-dependent API, a function for changing the status of use of the service (hereinafter,  
15 referred to as a "service use status operation function"). Based on the service use status operation function, whether the user utilizes an individual service with the terminal device 130 is designated, and the process that is to be carried out by the terminal device 130 for providing the service is controlled so as to be  
20 activated or ceased. Specifically, the process includes a preprocess, such as initialization of the execute form *DE* or internal data of the identified execute form *DEi*, and reception of necessary information, and conclusion of a service use agreement, billing, and user registration, which are conducted with respect  
25 to a service provision portion via a delivery system.

Specific examples of the general API include operation of an input/output device, such as an on-screen display or a keyboard entry with the terminal device reception portion 130, and data reading/writing from/to a temporary storage device, such as a RAM,  
5 or a secondary storage device, such as a HDD. In an exemplary case where an on-screen display is a resource of the general API, if on-screen displays corresponding to a plurality of services occur simultaneously, it is conceivable that conflict occurs between services. However, in the present embodiment, if a  
10 constraint in which only one service actually occupies the screen at a time is executed by the general resource manager 135 or an API call method, no conflict actually occurs to any execute form *DE*.

The general resource manager 135 stores and manages the  
15 general resource. Moreover, the general resource manager 135 references and operates the general resource based on API call *Capi* which is inputted from the resource selector 134. For example, ~~if~~ when an API for screen drawing is called, an instruction is issued to a graphics display device which is a general resource  
20 for carrying out screen drawing.

The service-dependent resource manager 136 stores and manages the service-dependent resource. It references and operates service-dependent resource *RS* based on API call *Capi* which is inputted from the resource selector 134. Also, it performs  
25 a management process of the service-dependent resource *RS* based

on associated information *IS* inputted from the downloader 131.

Referring to FIG. 3, a service-dependent resource management table *Trs* which is generated for managing the service-dependent resource *RS* stored in the service-dependent resource manager 136 is described. As illustrated in ~~the figure~~ FIG. 3, the service-dependent resource management table *Trs* is a database configured in a matrix with at least a plurality of rows *L1* through *Ln* indicating *n* types of services *S1* through *Sn* and two columns *C1* and *C2* indicating the status of use of each service *S*. Specifically, in ~~the figure~~ FIG. 3, row *L1* corresponds to service *S1*, row *L2* corresponds to service *S2*, row *Ln* corresponds to service *Sn* (in this case, *n* is a natural number equal to or more than 3). Column *C1* corresponds to the service identification information *Es*, and column *C2* corresponds to the status of use.

More specifically, as schematically shown in FIG. 2, values in columns *C1* and *C2* are determined and written based on *Sn* of the service identification information *Es(Sn)* and subsidiary information *an*. It is understood that in the example shown in FIG. 3, service *S1* indicated in row *L1* is "NOT USED", service *S2* indicated in row *L2* is "USED", and service *Sn* indicated in row *Ln* is "USED". In this manner, rows *L1* through *Ln* are respectively provided for storing information for identifying services of different services *S1* through *Sn*. In this context, rows *L1* through *Ln* (row *Lo*) are referred to as "service identification rows".

Next, an operation for adding a new service identification

row is described. If the downloader 131 receives a service (identified execute form *DEi*), a service identification row for defining a service-dependent resource *RS* to which execute form *DE* stored in the identified execute form storage device 132  
5 corresponds is added to the service-dependent resource management table *Trs*. This process automatically introduces the service to the terminal device 130, so that the new service is registered and managed in the service-dependent resource manager 136.

~~Hereinbelow, referring~~ Referring to FIG. 4, an operation  
10 of a new service registration/management routine by the service-dependent resource manager 136 is described below. An identified execute form *DEi* (execute form *DE* and associated information *IS*) corresponding to a new service is sent out from the service provision source 110 to the terminal device 130, and  
15 first inputted to the downloader 131. The downloader 131 extracts the associated information *IS* from the identified execute form *DEi*, and outputs it to the service-dependent resource manager 136. Then, in the service-dependent resource manager 136, the operation of the present routine starts at the time the associated information  
20 *IS* is inputted.

Accordingly, at step S502, it is determined whether the associated information *IS* has been inputted to the service-dependent resource manager 136. If it has not been inputted, "No" is assumed, and the process of the present step  
25 is repeated. On the other hand, in the case of "Yes", the procedure

proceeds to the next step S504. Specifically, a new service registration/management process does not substantially start until the service-dependent resource manager 136 receives the associated information *IS* from the downloader 131.

5       At step S504, it is determined whether service  $S_{\underline{L}}$  indicated by service identification information  $E_s$  of the associated information *IS* received at step S502, has already been registered in the service-dependent resource management table *Trs* stored in the service-dependent resource manager 136. If the service is  
10 not included, i.e., not registered, "No" is assumed, and the procedure proceeds to the next step S506.

At step S506, in the service-dependent resource manager 136, a new service identification row ( $L_{n+1}$ ) corresponding to the new service is added to the service-dependent resource management table  
15 *Trs*. The following description is given by taking as an example the service-dependent resource management table *Trs* shown in FIG. 3. Since the service-dependent resource management table *Trs* has registered therein, services  $S_1$  through  $S_n$ , the service identification row  $L(n+1)$  is added in order to register a new service  
20  $S(n+1)$ . Then, the procedure proceeds to the next step S508.

At step S508,  $S(n+1)$  which is a value for identifying the service  $S(n+1)$  is entered in row  $L(n+1)$ , column  $C_1$  based on the service identification information  $E_s$  contained in the associated information *IS* that has been received anew. Then, the procedure  
25 proceeds to the next step S510.

At step S510, "NOT USED" is entered in the cell for the status of use in row  $L(n+1)$ , column  $C2$  which has been added to the service-dependent resource management table  $Trs$ . This is because it is so arranged that "NOT USED" is set as an initial status when  
5 a new service (identified execute form  $DEi$ ) is received. However, it may be so arranged that "USED" is set as the initial status or trial use is offered as a demonstration for a predetermined time period, or the service identification setter 112 may provide, for each service, information indicating ~~either of these~~ whether  
10 the initial statuses is employed as the associated information  $IS$  (subsidiary information  $\alpha$ ). The present routine ends after the present step is completed.

In contrast, at the above step S504, if "Yes" is assumed, i.e., it is determined as being included, the above steps S506,  
15 S508 and S510 are skipped, and the procedure of the present routine is terminated. Specifically, if the service received by the downloader 131 is a service which has already been introduced, no service registration is required, and therefore the procedure of the present routine is immediately terminated.

20 Next, referring to FIG. 5, an operation of a service execution routine by the terminal device 130 is described. Specifically, in the terminal device 130, service execution is realized by executing an execute form  $DE$  corresponding to an API called by the executor 133. More specifically, a substantial procedure of  
25 the present routine starts at the time the executor 133 issues



API call *Capi* in order to execute the execute form *DE* contained in an identified execute form *DEi* which is inputted from the identified execute form storage device 132.

Accordingly, at step S512, the resource selector 134  
5 determines, based on the API call *Capi* issued by the executor 133, whether the called API is a service-dependent API. If it is the service-dependent API, "Yes" is assumed, and the procedure proceeds to the next step S514.

At step S514, the service-dependent resource manager 136  
10 obtains, from the executor 133, service identification information *Es* of a service associated with an execute form *DE* that is currently being executed. Then, the procedure proceeds to the next step S516.

At step S516, the service-dependent resource manager 136  
15 determines whether a service-dependent resource *RS* which is specified as a process target by the API call *Capi* corresponds to the service corresponding to the execute form *DE* detected at step S514 that is currently being executed. If it corresponds to the service corresponding to the execute form *DE* that is being  
20 executed, "Yes" is assumed, and the procedure proceeds to the next step S518.

At step S518, the service-dependent resource manager 136 uses the service-dependent API to process the service-dependent resource, and the procedure of the present routine ends.

25 In contrast, at the above step S512, if "No" is assumed,

i.e., it is determined as not being the service-dependent API (i.e., it is a general API), the procedure proceeds to step S520.

At step S520, the general resource manager 135 processes a general resource, and the procedure of the present routine is  
5 terminated.

Further, at the above step S516, if "No" is assumed, i.e., it does not correspond to the service corresponding to the execute form *DE* that is being executed, the procedure proceeds to step S521.

10 At step S521, an error process is performed, and thereafter the present routine ends. In this manner, settings are made so as not to permit an API process to be performed on a service-dependent resource which cannot be operated (No at S516) even in the case of the service to which the execute form *DE* that is being executed  
15 corresponds (Yes at S512).

In other words, in the present embodiment, only the service-dependent resource for the service associated with the execute form *DE* that is being executed is set so as to be operable. Accordingly, even if any API call is issued depending on the execute  
20 form *DE*, the service-dependent resource manager 136 prevents another service from being referenced or operated. Specifically, even if an execute form *DE* of a service which is intended to reference or operate another service is inputted, the procedure proceeds through step S516 to step S521, where an error process is performed  
25 to prevent such reference or operation, while making it possible

to detect such a demand.

As described above, in the present embodiment, at step S512, the resource selector 134 exerts control in such a manner that the process on the service-dependent resource can be operated only  
5 by the service-dependent API. This is described with reference to a software hierarchy of the terminal device 130 of a safe service extension platform *SEPl* shown in FIG. 6.

As shown in FIG. 6, if the terminal device 130 of the safe service extension platform *SEPl* is viewed in terms of its software  
10 structure, it is found that an OS layer realized by an OS which is basic software is present at the bottom. Provided on the OS layer are general resource management software, service-dependent resource management software, and identified execute form storage software, which respectively operate the general resource manager  
15 135, the service-dependent resource manager 136, and the identified execute form storage device 132. Further, provided on the general resource management software and the service-dependent resource management software is resource select software which operates the resource selector 134. The general resource management  
20 software, the service-dependent resource management software, the resource select software, and the identified execute form storage software constitute a middleware layer.

Provided on the resource select layer of the middleware layer is execute software (executor) for operating the executor 133,  
25 and provided on the identified execute form storage software is

download software (downloader) for operating the downloader 131.  
The execute software and the download software constitute an  
application layer.

Furthermore, provided on the execute software of the  
5 application layer are service  $S1-Sn$  execute forms which execute  
services  $S1$  through  $Sn$ , respectively, and constitute a content  
layer.

As is apparent from the software structure shown in FIG.  
6, in the safe service extension platform  $SEP1$ , execute form  $DE$   
10 of a service is not able to reference or operate a resource which  
is called by an API through the medium of the resource selector.  
Accordingly, as for the service-dependent resource, it is required  
to call a service-dependent API, wherein referencing or operation  
~~is~~are not possible if not via the service-dependent resource  
15 manager 136.

Next, an operation of changing a newly added service into  
a state that is actually used is briefly described with reference  
to an exemplary screen image shown in FIG. 7 which is presented  
to the user by the safe service extension platform  $SEP1$ . FIG.  
20 7 shows an exemplary screen image displayed by the execute form  
 $DE$  to prompt the user as to whether he/she wants to start using  
a new service.

Screen image  $SM$  is an exemplary screen image presented when  
the executor 133 executes an execute form  $DE$  executing a new service  
25 "MY NEWS SERVICE". On the screen image  $SM$ , button  $BY$  for declaring

the use of the service and button *BN* for declaring no intention of use are arranged. The user operates an input device to select the button *BY*, thereby starting the service.

Here, an operation in the case where the button *BY* is selected is described. The button *BY* is programmed in the execute form *DE* so as to activate the service-dependent API to declare the start of using the service. Accordingly, if the button *BY* is selected, the service-dependent API is delivered through the resource selector 134 to the service-dependent resource manager 136, so that the value entered in the cell for the status of use of the service corresponding to the service-dependent resource *RS* in the service-dependent resource management table *Trs* is rewritten to the "USED".

Note that although the start of simply using the service is described in relation to the example shown in FIG. 7, it is also possible to conclude a service use agreement with a service provision portion, conduct user registration, or start an automatic storing process before viewing a storage-type data broadcast.

In this manner, it is possible to perform a service-related operation, such as the transition of the status of whether the service is used or not unused, through the interaction with the user based on the execute form *DE* of the service itself. Further, even if another service is executed with an execute form *DE* with any malicious intent, it is possible to avoid any adverse effect, e.g., a malfunctioning or hang-up, on the service or the platform.

As described above, in the safe service extension platform *SEP1* according to the first embodiment of the present invention, while maintaining the service extensibility, it is possible to achieve complete safety in which any execute form *DE* that can be  
5 assumed does not cause a false process to affect another service or the platform itself, rather than obtaining unreliable safety in which if the identity of the distributor of that execute form *DE* seems to be authentic, it is analyzed that execute form *DE* does not include a code which might cause a false process.

10 (Second Embodiment)

Hereinafter, referring to FIGs. 8, 9, and 11, a safe service extension platform according to a second embodiment of the present invention is described. As shown in FIG. 8, a safe service extension platform *SEP2* according to the present embodiment is  
15 such that the service provision source 110 of the safe service extension platform *SEP1* shown in FIG. 1 is changed to a service provision source 210, and the terminal device 130 is changed to a terminal device 230.

The service provision source 210 is such that the service  
20 identification setter 112 of the service provision source 110 is replaced with a metaservice designator 212. The terminal device 230 is such that the executor 133 of the terminal device 130 is replaced with an executor 233, and a metaservice determiner 234 is additionally provided between the resource selector 134 and  
25 the service-dependent resource manager 136.

The terminal device 230 is such that the downloader 131 of the terminal device 130 according to the first embodiment is replaced with a downloader 231, the identified execute form storage device 132 is replaced with an identified execute form storage device 232, the executor 133 is replaced with the executor 233, and the metaservice determiner 234 is additionally provided between the resource selector 134 and the service-dependent resource manager 136.

In the service provision source 210, the metaservice designator 212 is such that the above-described service identification setter 112 is provided with a metaservice designation information generation function. Specifically, similar to the service identification setter 112, the metaservice designator 212 generates associated information *IS* which indicates a subsidiary matter, such as an attribute of execute form *DE*, and also generates metaservice designation information *IS<sub>m</sub>* for designating an execute form *DE* that is to be associated with a metaservice.

The metaservice is the only one of the above services in which it is possible to carry out service extension, such as changing of service functions/features, e.g., the start/end of the use of the service actually used by the user, and addition of a new service. The metaservice exists for the purpose of the service extension. In this context, herein, the service *S* as described in the first embodiment and metaservice *S<sub>meta</sub>* of the present embodiment are



distinguished from each other.

Associated information *IS* is added to execute form *DE* to generate identified execute form *DEi*, and metaservice designation information *ISm* is added to the execute form *DE* to generate  
5 metaservice execute form *DEm*. Specifically, the identified execute form *DEi* and the metaservice execute form *DEm* are collectively outputted from the metaservice designator 212. Then, the identified execute form *DEi* and the metaservice execute form *DEm* are inputted to the terminal device 230 via the sender 113  
10 and the delivery system 120. Then, the downloader 231 of the terminal device 230 outputs the identified execute form *DEi* and the metaservice execute form *DEm* to the identified execute form storage device 232. Then, the downloader 231 extracts the associated information *IS* from the identified execute form *DEi*,  
15 and also extracts metaservice designation information *ISm* from the metaservice execute form *DEm*, and they are outputted to the service-dependent resource manager 236.

FIG. 9 shows how the identified execute form *DEi* and the metaservice execute form *DEm*, which are outputted from the  
20 metaservice designator 212, are stored in the identified execute form storage device 232. In the example shown in ~~the figure~~ FIG. 9, as in the first embodiment shown in FIG. 2, identified execute form *DEi(S1)*, *DEi(S2)*, and *DEi(Sn)* respectively corresponding to service *S1*, and services *S2* through *Sn* (where *n* is an arbitrary  
25 natural number) are illustrated. Note that in ~~the figure~~ FIG. 9,

the first metaservice execute form  $DEm(1)$  is shown in the position for identified execute form  $DEi(S3)$  corresponding to service  $S3$ . The metaservice execute form  $DEm(1)$  is such that an execute form  $DE$  is assigned with metaservice designation information  $ISm(1)$  which indicates that the execute form corresponds to a metaservice.

The metaservice execute form  $DEm(1)$  includes metaservice designation information  $ISm$  consisting of service identification information  $Es(Sm1)$  and subsidiary information  $\alpha m1$ , each of which corresponds to metaservice  $m1$ , and it also includes an execute form  $DE$ . Specifically, the service identification information  $Es(Sm1)$  associates the execute form  $DE$  with metaservice  $1$ . As such, except that " $Sm1$ " of the service identification information  $Es(Sm1)$  defines the metaservice  $1$ , the metaservice designation information  $ISm$  is basically the same as the associated information  $IS$ .

Specifically, as described above, the metaservice  $Sm$  is one of the services  $Sn$ , therefore the metaservice execute form  $DEm$  can also be represented by identified execute form  $DEi(Sm)$ . Accordingly, the metaservice designation information  $ISm$  may be referred to by the generic name "associated information  $IS$ ", but for the purpose of clarifying the feature of the present embodiment, herein, the metaservice designation information  $ISm$  is distinguished from the associated information  $IS$ . Further, the service identification information  $Es$  corresponding to a metaservice is referred to as "metaservice identification

information *Esm* so as to be distinguished from the service identification information *Es* corresponding to the execute form *DE*.

The operation of the identified execute form storage device 232 is basically the same as that of the identified execute form storage device 132 as described above in the first embodiment. However, it should be noted that the identified execute form storage device 232 stores the identified execute form *DEi* and the metaservice execute form *DEm*, and in response to a demand, the identified execute form *DEi* or the metaservice execute form *DEm* is outputted to the executor 233.

The executor 233 extracts the service identification information *Es* from the identified execute form *DEi*, and also extracts the service identification information *Esm* from the metaservice execute form *DEm*, and they are outputted to the metaservice determiner 234.

The metaservice determiner 234 outputs API call *Capi* to the service-dependent resource manager 136 based on the API call *Capi* inputted from the resource selector 134, and the service identification information *Es* and the service identification information *Esm*, which are inputted from the executor 233, only when the execute form *DE* that is being executed is associated with the metaservice.

The service-dependent resource manager 136 stores service-dependent resource *RS*, and manages the service-dependent

resource *RS* by the service-dependent resource management table  
*Trs*. Note that the service-dependent resource *RS* stored in the  
service-dependent resource manager 136 and the service-dependent  
resource management table *Trs* ~~therefor~~therefore may be the same  
5 as those described in the first embodiment with reference to FIG.  
3.

Then, in response to the API call *Capi* inputted via the  
metaservice determiner 234, for example, the service-dependent  
resource manager 136 references or operates the service-dependent  
10 resource *RS* stored in the service-dependent resource manager 136.  
Also, it recognizes the details of services to which the execute  
forms *DE* correspond, based on the associated information *IS*  
provided from the downloader 231.

In the addition of a new service, at the time the  
15 service-dependent resource manager 136 detects the presence of  
a new service which is not registered in the service-dependent  
resource management table *Trs*, based on the associated information  
*IS* and the metaservice designation information *ISm* which are  
inputted from the downloader 231, an identification row for that  
20 service is added and the details thereof are written therein.  
Specifically, in the service-dependent resource management table  
*Trs*, the details of the metaservice ~~is~~are written in column *C1*,  
but if focusing only on the procedure of adding the service  
identification row, the details of a process ~~is~~are the same as  
25 those in the first embodiment.

Next, referring to a flowchart shown in FIG. 10, an operation of a service execution routine by the terminal device 230 is described. Specifically, in the terminal device 230, the service execution is realized by executing an execute form *DE* corresponding to an API called by the executor 233. Specifically, the procedure of the present routine starts at the time the executor 233 issues an API call *Capi* in order to implement execute forms *DE* contained in identified execute form *DEi* and metaservice execute form *DEm*, which are inputted from the identified execute form storage device 232.

Note that the structure of the flowchart shown in FIG. 10 is similar to that of the flowchart shown in FIG. 5 except that the "OBTAIN SERVICE IDENTIFICATION INFORMATION *ES* FOR EXECUTE FORM *DE* THAT IS BEING EXECUTED" step S514 is replaced with the "OBTAIN SERVICE IDENTIFICATION INFORMATION *ES* OR SERVICE IDENTIFICATION INFORMATION *Esm* FOR EXECUTE FORM *DE* THAT IS BEING EXECUTED" step S1014, and the "DETERMINE WHETHER IT IS OPERATION FOR SERVICE THAT IS BEING EXECUTED?" step S516 is replaced with the "DETERMINE WHETHER IT IS-OPERATION FOR METASERVICE THAT IS BEING EXECUTED?" step S1016. The descriptions given below mainly focus on the operation unique to the present embodiment.

At step S512, if the resource selector 134 determines, based on API call *Capi* issued by the executor 233, that a called API is a service-dependent API, then the procedure proceeds to step S1014.

At step S1014, the metaservice determiner 234 reads, from the executor 233, service identification information *Es* or metaservice identification information *Esm* corresponding to the execute form *DE* that is currently being executed, and the procedure  
5 proceeds to the next step S1016.

At step S1016, it is determined whether the execute form *DE* that is being executed is associated with the metaservice. In the case of "No", the present routine is terminated after the above-described error process step S521. On the other hand, if  
10 the execute form *DE* that is being executed is associated with the metaservice, "Yes" is assumed, the procedure proceeds to the "PROCESS SERVICE-DEPENDENT RESOURCE" step S518, and thereafter the present routine is terminated.

Note that in the case of the execute form *DE* of the metaservice that is being executed (Yes at step S1016), service-dependent  
15 resources for all services are processed at step S518.

As described above, in the second embodiment, if the execute form *DE* is the metaservice, then service-dependent APIs for all services can be executed. Accordingly, a list of services  
20 available from the service provision portion is displayed in the window of the execute form *DE* of the metaservice, and the service extension, such as changing of a service function/feature or an addition of a new service, is achieved on the displayed list.

(Third Embodiment)

25 Next, referring to FIGs. 11, 12, and 13, a safe service

extension platform according to a third embodiment of the present invention is described in detail. As shown in FIG. 11, a safe service extension platform *SEP3* according to the present embodiment is such that the service provision source 110 of the safe service extension platform *SEP1* shown in FIG. 1 is changed to a service provision source 310, and the terminal device 130 is changed to a terminal device 330.

The service provision source 310 is such that the service identification setter 112 of the service provision source 110 is replaced with a service identification setter 312, and a service identification parent/child manager 314 is additionally provided. In the case where there are parent/child relationships between separate services, the service identification parent/child manager 314 manages such relationships as parent/child relationships between pieces of identification information *Es*. Further, service parent/child designation information *ISh* which indicates managed parent/child relationships is outputted to the service identification setter 312.

The terminal device 330 is such that the downloader 131 of the terminal device 130 is replaced with a downloader 331, the identified execute form storage device 132 is replaced with an identified execute form storage device 332, the executor 133 is replaced with an executor 333, and a parent/child determiner 334 is additionally provided between the resource selector 134 and the service-dependent resource manager 136.



In the service provision source 310, a parent/child relationship between services managed by the service identification parent/child manager 314 is defined as a relationship in which a service-dependent resource *Rs* of a child service can be operated by a parent service. Note that as the necessity arises, the names "parent service *Sp*", "child service *Sc*", and "service-dependent resource *RSc* of the parent service" are used to identify each of them. For example, for a parent service corresponding to the service category "music content distribution service", there are child services corresponding to individual service types, such as a "Matsushita music distribution service", a "Teichiku music distribution service", and an "ep-channel music service".

The service identification setter 312 is such that the above service identification setter 112 is provided with a parent/child service identification information generation function. Specifically, similar to the service identification setter 112, the service identification setter 312 generates associated information *IS* which indicates a subsidiary matter, such as an attribute of execute form *DE*. Further, based on service parent/child information *Ih* supplied from the service identification parent/child manager 314, the service identification setter 312 generates service parent/child information *Esc*. For example, service parent/child designation information *ISh(S1-1)* is generated based on the service

parent/child information  $I_h$ . Service parent/child information  $Esc(S1-1)$  defines that the service is a child service of parent service  $S1$ .

The associated information  $IS$  is added to the execute form  $DE$  to generate an identified execute form  $DEi$ , and the service parent/child designation information  $ISh$  is added to the execute form  $DE$  to generate a parent/child identified execute form  $DEc$ . Specifically, the identified execute form  $DEi$  and the parent/child identified execute form  $DEc$  are collectively outputted from the service identification setter 312. Then, the identified execute form  $DEi$  and the parent/child identified execute form  $DEc$  are inputted to the terminal device 330 via the sender 113 and the delivery system 120. Then, the downloader 331 of the terminal device 330 outputs the identified execute form  $DEi$  and the parent/child identified execute form  $DEc$  to the identified execute form storage device 332. Further, the downloader 331 extracts the associated information  $IS$  from the identified execute form  $DEi$ , and extracts the service parent/child designation information  $ISh$  from the parent/child identified execute form  $DEc$ , and they are outputted to the service-dependent resource manager 136.

FIG. 12 shows how the identified execute form  $DEi$  and the parent/child identified execute form  $DEc$ , which are outputted from the service identification setter 312, are stored in the identified execute form storage device 332. In the example shown in the figure, as in the first embodiment shown in FIG. 2, identified execute

forms  $DEi(S1)$ ,  $DEi(S2)$ , and  $DEi(Sn)$  respectively corresponding to service  $S1$ , and services  $S2$  through  $Sn$  (where  $n$  is an arbitrary natural number) are illustrated. Note that in ~~the figure~~ FIG. 12, the first parent/child identified execute form  $DEc(1)$  is shown in the position for identified execute form  $DEi(S3)$  corresponding to service  $S3$ . The parent/child identified execute form  $DEc(1)$  is such that an execute form  $DE$  is assigned with service parent/child designation information  $ISh$  which indicates that the execute form corresponds to a child service.

10       The parent/child identified execute form  $DEc(1)$  includes service parent/child designation information  $ISh(1)$  consisting of service identification information  $Es(Sc1)$  and subsidiary information  $\alpha c1$ , each of which corresponds to parent service  $Sp1$ , and it also includes an execute form  $DE$ . Specifically, the parent/child service identification information  $Esc$  associates 15 the execute form  $DE$  with child service  $Sc1$  corresponding to the parent service  $Sp1$ . As such, the service parent/child designation information  $ISh$  is basically the same as the associated information  $IS$  except that " $Sp1$ " of the service identification information  $Es(Sp1)$  defines child service 1. 20

Specifically, as described above, the child service  $Sc$  is one of the services  $Sn$ , therefore the parent/child identified execute form  $DEc$  can also be represented by identified execute form  $DEi(Sc)$ . Accordingly, the service parent/child designation information  $ISh$  may be referred to by the generic name "associated 25

information *IS*", but for the purpose of clarifying the feature of the present embodiment, herein, the service parent/child designation information *ISh* is distinguished from the associated information *IS*. Further, the service identification information *Es* which defines the child service *Sc* corresponding to the parent service *Sp* is referred to as "parent/child service identification information *Esc*" so as to be distinguished from the service identification information *Es* corresponding to the execute form *DE*.

10       The operation of the identified execute form storage device 332 is basically the same as that of the identified execute form storage device 132 as described above in the first embodiment. Note that the identified execute form storage device 332 stores the identified execute form *DEi* and the parent/child identified execute form *DEc*, and in response to a demand, the identified execute form *DEi* or the parent/child identified execute form *DEc* is outputted to the executor 333.

20       The executor 333 extracts the service identification information *Es* from the identified execute form *DEi*, and also extracts the parent/child service identification information *Esc* from the parent/child identified execute form *DEc*, and they are outputted to the parent/child determiner 334.

25       The parent/child determiner 334 outputs API call *Capi* to the service-dependent resource manager 136 based on the API call *Capi* inputted from the resource selector 134, and the service

identification information *Es* and the parent/child service identification information *Esc*, which are inputted from the executor 333, only when the execute form *DE* that is being executed is an ancestor (a parent, a parent's parent, a parent's parent's parent, ...) of the service for the service-dependent resource targeted for processing by the API call *Capi*.

Specifically, the parent/child determiner 334 obtains, from the executor 333, the parent/child service identification information *Esc* for the execute form *DE* that is being executed, and also obtains the API call *Capi* issued by the executor 333 via the resource selector 134. Further, the service parent/child designation information *ISh* which is information for determining a parent/child relationship between services is obtained from the downloader 331. Then, it is determined whether the service indicated by the parent/child service identification information *Esc* is an ancestor of the service indicated by the service parent/child designation information *ISh*. Then, if it is determined to be the ancestor, the service-dependent resource manager 136 is notified of a request to call the service-dependent API (API call *Capi*), while no notification is given if it is determined not to be the ancestor.

Next, referring to a flowchart shown in FIG. 13, an operation of a service execution routine by the terminal device 330 is described. Specifically, the procedure of the present routine starts at the time the executor 333 in the terminal device 330

issues an API call *Capi* in order to execute an execute form *DE* corresponding to an API that is to be called and an execute form *DE* contained in the parent/child identified execute form *DEc*.

Note that the structure of the flowchart shown in FIG. 13  
5 is similar to that of the flowchart shown in FIG. 5 except that the "OBTAIN SERVICE IDENTIFICATION INFORMATION *ES* FOR EXECUTE FORM *DE* THAT IS BEING EXECUTED" step S514 is replaced with the "OBTAIN SERVICE IDENTIFICATION INFORMATION *ES* OR PARENT/CHILD SERVICE IDENTIFICATION INFORMATION *Esc* FOR EXECUTE FORM *DE* THAT IS BEING  
10 EXECUTED" step S1314, and the "DETERMINE WHETHER IT IS OPERATION FOR SERVICE THAT IS BEING EXECUTED?" step S516 is replaced with the "DETERMINE WHETHER IT IS OPERATION OF METASERVICE THAT IS BEING EXECUTED?" step S1316. The descriptions given below mainly focus on the operation unique to the present embodiment.

15 At step S512, if the resource selector 134 determines, based on API call *Capi* issued by the executor 333, that a called API is a service-dependent API, then the procedure proceeds to step S1314.

At step S1314, the parent/child determiner 334 reads, from  
20 the executor 333, service identification information *Es* or parent/child service identification information *Esc*, which corresponds to the execute form *DE* that is currently being executed, and the procedure proceeds to the next step S1316.

At step S1316, the parent/child determiner 334 determines  
25 whether the service corresponding to the execute form *DE* that is

being executed is an ancestor service of a service corresponding to the service-dependent resource that is targeted for processing by the service-dependent API call *Capi*. In the case of "No", the present routine is terminated after the above-described error process step S521. On the other hand, if the execute form *DE* that is being executed is an ancestor of the service that is being executed, "Yes" is assumed, and the present routine ends after the procedure proceeds to the "PROCESS SERVICE-DEPENDENT RESOURCE" step S518.

Note that at step S518, the service-dependent resource manager 136 processes the service-dependent resource corresponding to the service-dependent API call *Capi*. Specifically, it is so managed that a service-dependent resource for an offspring (a child, a child's child, a child's child's child, etc....) of a service of the execute form *DE* that is currently being executed can be processed.

(Fourth Embodiment)

Next, referring to FIGs. 14, 15, 16, and 17, a safe service extension platform according to a fourth embodiment of the present invention is described. As shown in FIG. 8, a safe service extension platform *SEP4* according to the present embodiment is such that the service provision source 110 of the safe service extension platform *SEP1* shown in FIG. 1 is changed to a service provision source 410, and the terminal device 130 is changed to a terminal device 430.

The service provision source 410 is such that the execute



form provider 111 of the service provision source 110 is replaced with a content provider 411, and the service identification setter 112 is replaced with a control content designator 412. The terminal device 430 is such that the downloader 131 of the terminal device 130 is replaced with a content downloader 431, the identified execute form storage device 132 is replaced with a content storage device 432, the executor 133 is replaced with an executor 433, and a control content determiner 434 is additionally provided between the resource selector 134 and the service-dependent resource manager 136.

The content provider 411 stores execute form *DE*, which implements a service, and content *DC*, which is data generated so as to be interpreted by the execute form *DE* and presented to the user, and they are outputted on demand. The execute form *DE* meets requirements that are to be satisfied by the content *DC*. For example, both the execute form *DE* and the content *DC* are written in markup language which can include a script description for programming sequential operation procedures. The script language may be a language such as Java (R)-based JavaScript or ECMAScript. Also, the markup language may be an HTML language or a BML language.

The control content designator 412 assigns associated information *ISC* indicative of control content to a control content from among contents *DC* outputted from the content provider 411, and outputs it as control content *DCc*. The control content *DCc* is defined as being content *DC* generated as an execute form *DE*

associated with a service.

The content downloader 431 receives the content *DC* and the control content *DCc*, which are transmitted from the delivery system 120, and writes the received information into the content storage  
5 device 432.

Since the delivery system 120 transmits the execute form *DE* as a kind of content *DC*, the content downloader 431 may have a function of storing the content *DC*.

The content downloader 431 controls content storage based  
10 on information held as a service-dependent resource in the service-dependent resource manager 136 and indicating whether to automatically download service content.

Specifically, in the case where a target service should be automatically downloaded, the content downloader 431 stores all  
15 content *DC* related to that service, including the control content *DCc*. On the other hand, in the case where it should not be automatically downloaded, only the control content *DCc* is stored.

The content storage device 432 stores the content *DC*. While information stored in the identified execute form storage device  
20 132 as described in the first embodiment is the execute form *DE*, the content storage device 432 stores the content *DC*. Note that the content *DC* includes the control content *DCc*.

FIG. 15 shows how the content *DC* outputted from the control content designator 412 and the associated information *ISC* are  
25 stored in the content storage device 432. In the example shown

in the figure FIG. 15, for service  $S1$ ,  $C(S1, DE)$ , which is a control content  $DCc$ , and  $C(S1, 1)$ ,  $C(S1, 2)$ , and  $C(S1, 3)$ , which are contents  $DC$ , are held in the content storage device 432.  $C(S1, E)$  which is the control content  $DCc$  is executed by the executor 433, such  
5 that  $C(S1, 1)$ ,  $C(S1, 2)$ , and  $C(S1, 3)$ , which are the contents  $DC$ , are read and presented to the user. Specifically,  $C(S1, DE)$  which is a control content  $DCc$  operates in a manner equivalent to a so-called browser for  $C(S1, 1)$ ,  $C(S1, 2)$ , and  $C(S1, 3)$  which are the contents  $DC$ .

10 The control content determiner 434 determines, based on an output of the executor 433, whether the content  $DC$  that is being executed is the control content  $DCc$ . Then, only in the case of the control content  $DCc$ , a request for a service-dependent API from the resource selector 134 is transmitted to the  
15 service-dependent resource manager 136.

FIG. 16 is an exemplary service-dependent resource table  $Trs4$  stored in the service-dependent resource manager 136 in the present embodiment. Although the service-dependent resource table  $Trs4$  is similar to the service-dependent resource management  
20 table  $Trs$  for the first embodiment shown in FIG. 3, column  $C2$  holds, for each service, information which indicates whether the content downloader 431 should automatically download content  $DC$ .

Next, referring to a flowchart shown in FIG. 17, an operation of a routine of executing control content  $DCc$  by the terminal device  
25 430 is described. Specifically, the procedure of the present

routine starts at the time the executor 433 in the terminal device 430 issues API call *Capi* in order to execute control content *DCc* for an API that is to be called.

Note that the structure of the flowchart shown in FIG. 17 is similar to that of the flowchart shown in FIG. 5 except that the "OBTAIN SERVICE IDENTIFICATION INFORMATION *ES* FOR EXECUTE FORM *DE* THAT IS BEING EXECUTED" step S514 is replaced with the "OBTAIN SERVICE IDENTIFICATION INFORMATION *ES* FOR CONTENT *DC* THAT IS BEING EXECUTED" step S1714, and the "DETERMINE WHETHER IT IS OPERATION FOR SERVICE THAT IS BEING EXECUTED?" step S516 is replaced with the "DETERMINE WHETHER IT IS CONTROL CONTENT OPERATION FOR SERVICE THAT IS BEING EXECUTED?" step S1716. The descriptions given below mainly focus on the operation unique to the present embodiment.

At step S512, if the resource selector 134 determines, based on API call *Capi* issued by the executor 433, that a called API is a service-dependent API, then the procedure proceeds to step S1714.

At step S1714, the control content determiner 434 reads, from the executor 433, service identification information *Es* for the content *DC* that is currently being executed, and the procedure proceeds to the next step S1716.

At step S1716, the control content determiner 434 determines whether the content *DC* that is being executed is a control content corresponding to a service to which the content *DC* corresponds and which corresponds to the service-dependent resource that is

targeted for processing by the service-dependent API call *Capi*.  
In the case of "No", the present routine is terminated after the  
above-described error process step S521. On the other hand, if  
the content *DC* that is being executed is an ancestor of the service  
5 that is being executed, "Yes" is assumed, and the present routine  
ends after the procedure proceeds to the "PROCESS SERVICE-DEPENDENT  
RESOURCE" step S518.

Note that at step S518, the service-dependent resource  
manager 136 processes the service-dependent resource  
10 corresponding to the service-dependent API call *Capi*.

According to the safe service extension platform disclosed  
herein, it is possible to realize new dimensional safety in which  
false access by execute form *DE* which implements a service can  
be eliminated without the need to deny that a process which might  
15 cause the false access is included in the execute form *DE*.

Specifically, it is possible to eliminate false access which  
is a process causing behavior with adverse effects on normal service  
reception, such as a change of the status of another service, data  
corruption, a system down of the platform itself, without the need  
20 to infer from the authenticity of the distributor of the execute  
form *DE* that the execute form *DE* includes a process which might  
cause false access.

Further, in addition to the above described nature, it is  
possible to change or add the execute form *DE* to implement a function  
25 which achieves service extension, such as a change of a service

function/feature or addition of a new service.

Thus, it is possible to simultaneously realize unprecedented new dimensional safety and operability in a conventional platform which can extend a service.

5

#### INDUSTRIAL APPLICABILITY

As described above, the present invention is useful in an unprecedented and completely new safe service extension platform which realizes three features: "service extensibility",  
10 "retention of service safety" and "seamless service extension operation".

## ABSTRACT

~~An object of the present invention is to provide a~~The present  
invention is directed to a service-extensible, completely new "safe  
5 service extension platform" in which false access, by an execute  
form which implements a digital content providing service, can  
be eliminated without the need to deny ~~that a~~ process which might  
cause the false access ~~is included in the execute form~~. ~~A~~The  
safe service extension platform ~~(SEP)~~, in which services ~~(S)~~ are  
10 associated with an execute form ~~(DE)~~ and the services ~~(S)~~ are  
extended by changing or adding the execute form ~~(DE)~~, ~~comprises~~  
includes a service-dependent API for extending the services. The  
~~and the~~ service extension from the execute form ~~(DE)~~ is carried  
out only by calling the service-dependent API.